

High Brightness TFT´s		
	Panel + Inverter + Controller + OSD	Panel + Inverter + Controller + OSD + Gehäuse + NT
Spezifikation	10,4"	10,4"
Anzeigebereich (BxH):	211,2 x 158,4 mm	211,2 x 158,4 mm
max. Auflösung:	800 x 600 (SVGA)	800 x 600 (SVGA)
Pixelgröße:	0,264 (H) x 0,264 (V)	0,264 (H) x 0,264 (V)
Video:	RGB analog	RGB analog
Synchronisation:	LVDS	LVDS
Videoanschluss:	15pol. HD Sub-D, S-Video, DVI	15pol. HD Sub-D, S-Video, DVI
Farben:	262,144	262,144
Helligkeit:	1500 cd/m ²	1500 cd/m ²
Kontrast:	500 : 1	500 : 1
Blickwinkel:	60° ~ -60° (H), 40° ~ - 60° (V)	60° ~ -60° (H), 40° ~ - 60° (V)
Reaktionszeit:	35 mS (typ.)	35 mS (typ.)
OSD- Bedienelemente:	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management
Anti- Reflektionsglas:		optional
Touchscreen:		optional
Stromversorgung:	12V DC	115/230 V
Stromverbrauch:	30 W	30 W
Gewicht:	0,75 kg	3,15 kg
Abmessungen (BxHxT):	243 x 184 x 27,2 mm	340 x 228 x 54,2 mm