



<p>High Brightness TFT´s</p>	 <p>Panel + Inverter + Controller + OSD</p>	 <p>Panel + Inverter + Controller + OSD + Gehäuse + NT</p>
Spezifikation	12,1"	12,1"
Anzeigebereich (BxH):	245,76 x 184,32 mm	245,76 x 184,32 mm
max. Auflösung:	1024 x 768 (XGA)	1024 x 768 (XGA)
Pixelgröße:	0,24 (H) x 0,24 (V)	0,24 (H) x 0,24 (V)
Video:	RGB analog	RGB analog
Synchronisation:	LVDS	LVDS
Videoanschluss:	15pol. HD Sub-D, S-Video, DVI	15pol. HD Sub-D, S-Video, DVI
Farben:	262,144	262,144
Helligkeit:	800 cd/m ² / 1250 cd/m²	800 cd/m ² / 1250 cd/m²
Kontrast:	500 : 1	500 : 1
Blickwinkel:	70° ~ -70° (H), 55° ~ - 70° (V)	70° ~ -70° (H), 55° ~ - 70° (V)
Reaktionszeit:	50 mS (max.)	50 mS (max.)
OSD- Bedienelemente:	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management
Anti- Reflektionsglas:		optional
Touchscreen:		optional
Stromversorgung:	12V DC	115/230 V
Stromverbrauch:	32 W	32 W
Gewicht:	0,8 kg	3,07 kg
Abmessungen (BxHxT):	277,4 x 204,6 x 27 mm	338 x 278 x 59,3 mm