



<p>High Brightness TFT´s</p>	 <p>Panel + Inverter + Controller + OSD</p>	 <p>Panel + Inverter + Controller + OSD + Gehäuse + NT</p>
Spezifikation	15,1"	15,1"
Anzeigebereich (BxH):	304,128 x 228,096 mm	304,128 x 228,096 mm
max. Auflösung:	1024 x 768 (XGA)	1024 x 768 (XGA)
Pixelgröße:	0,297 (H) x 0,297 (V)	0,297 (H) x 0,297 (V)
Video:	RGB analog	RGB analog
Synchronisation:	LVDS	LVDS
Videoanschluss:	15pol. HD Sub-D, S-Video, DVI	15pol. HD Sub-D, S-Video, DVI
Farben:	262,144	262,144
Helligkeit:	800 cd/m ² / 1600 cd/m²	800 cd/m ² / 1600 cd/m²
Kontrast:	400 : 1	400 : 1
Blickwinkel:	70° ~ -70° (H), 50° ~ - 70° (V)	70° ~ -70° (H), 50° ~ - 70° (V)
Reaktionszeit:	16 mS (typ.)	16 mS (typ.)
OSD- Bedienelemente:	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management	Helligkeit, Kontrast, H/V Position Farben, Phase, Clock, Management
Anti- Reflektionsglas:		optional
Touchscreen:		optional
Stromversorgung:	12V DC	115/230 V
Stromverbrauch:	56,5W	56,5 W
Gewicht:	1,75 kg	3,92 kg
Abmessungen (BxHxT):	326,5 x 253,5 x 19,46 mm	389 x 317 x 51,1 mm