


15“ Industrie-TFT-LCD Einbauchassis/Open frame



Art.-Nr. F0415x0C

Displaydiagonale	15" TFT Active Matrix Panel
Displaygröße	304.1 x 228.1 mm
Punktdichte	0.297 x 0.297 mm
Anzeige-Modus	VGA 640 x 350 (70 Hz) VGA 720 x 400 (70 Hz) VGA 640 x 480 (60/72/75 Hz) SVGA 800 x 600 (60/72/75 Hz) XGA 1024 x 768 (60/72/75 Hz) MAC®. 832 x 624 (60/72/75 Hz)
Max. Auflösung	1024 x 768
Kontrast	400:1 (typ.)
Helligkeit	230 cd/m ² (typ.)
Reaktionszeit	15 mS (Rising), 10 mS (Falling)
Farben	16 Mio.
Blickwinkel	+80° ~ -80°(L/R), +80° ~ -80°(U/D)
Input Signal	R.G.B Analog 0.7V Peak-to-Peak TTL Positive or Negative
Schnittstellen	15Pin Mini D-sub
Bedienelemente	Power Switch, Menu, Select (up, Down), Adjust(+,-)
OSD	Kontrast, Helligkeit, Clock, Phase, H-Position , V-Position, Farb- Temperatur, Load default
Plug & Play	DDC1/2B
Audio System	optional
Video In	PAL/NTSC optional
S-Video/AV Connector	optional
Touchscreen	optional
Stromversorgung	Universal 90-240 V, 12 V / 35 W
Gehäuseabmessungen	frontseitig: B = 380 x H = 297 rückwärtig: B = 360 x H = 277 x T = 54 mm
Gewicht (netto)	7 Kg
Zertifizierung	FCC-B, CE, UL

Maßzeichnung 15" Industrie-TFT-LCD Einbauchassis/Open frame

